

Evergreen RCA/RCA 1m

39,00 €

Product gallery:



Product description:

Note: All cables in our Bridges - Falls Series place their left and right channels in a single jacket, and feature our Asymmetrical Double-Balanced geometry with separate high-quality positive and negative conductors. This design allows for a thin, flexible, and uniquely versatile high-performance cable that can be terminated with a variety of today's connections, including 3.5mm (male or female), DIN, and RCA. In Bridges - Falls, you'll find better metals and more sophisticated technologies — including Air-Tube insulation, Dielectric-Bias System, and Noise-Dissipation System — at lower prices than ever before. Do keep in mind, however, that, by necessity, the plugs on Bridges - Falls cables are fairly close together. If the L and R inputs of your components are more than 3" (7.6cm) apart, please consider models from our Rivers or Elements Series.

The Evergreen Point Floating Bridge connects Seattle, Washington (USA) to the Bellevue area across Lake Washington. Since opening in 1963, its 2,285 meters (7,497 ft) makes it the longest floating bridge in the world. The structure includes 33 pre-stressed concrete pontoons averaging 110 meters (360 ft) long and 18 meters (60 ft) wide.

SOLID LONG-GRAIN COPPER (LGC) CONDUCTORS: Solid conductors eliminate strand-interaction distortion. Evergreen's solid Long-Grain Copper allows a smoother and clearer sound than cables using regular OFHC (Oxygen-Free High-Conductivity) copper. OFHC is a general metal industry specification regarding "loss" without any concern for distortion. LGC has fewer oxides within the conducting material, less impurities, less grain boundaries, and definitely better performance.

FOAMED-POLYETHYLENE INSULATION: Any solid material adjacent to a conductor is actually part of an imperfect circuit. Wire insulation and circuit board materials all absorb energy (loss). Some of this energy is stored and then released as distortion. Evergreen uses air-filled Foamed-Polyethylene Insulation on both conductors because air absorbs next to no energy and Polyethylene is low-loss and has a benign distortion profile. Thanks to all the air in Foamed-PE, it causes much less of the out-of-focus effect common to other materials.

METAL-LAYER NOISE-DISSIPATION SYSTEM (NDS): 100% shield coverage is easy. Preventing captured RF Interference from modulating the equipment's ground reference requires AQ's Noise-Dissipation System. Noise-Dissipation System prevents a significant amount of RFI from reaching the equipment's ground plane.

ASYMMETRICAL DOUBLE-BALANCED GEOMETRY: Purpose designed for single-ended applications, Asymmetrical Double-Balanced Geometry offers a relatively lower impedance on the ground for a richer, and more dynamic experience. While many single-ended cable designs use a single path for both the ground and the shield, Double-Balanced designs separate the two for cleaner, quieter performance.

COLD-WELDED, GOLD-PLATED TERMINATIONS: This plug design allows for a connection devoid of solder, which is a common source of distortion. Because the ground shells are stamped instead of machined, the metal can be chosen for low distortion instead of machinability.